

CellXpert® CO₂ Incubators: C170i or C170?



Your Requirements	CellXpert C170i	CellXpert C170
Will you be cultivating cells under hypoxic / low O ₂ conditions?	Yes or maybe <input type="checkbox"/>	No <input type="checkbox"/>
Do you have to fulfill a requirement for 180 °C sterilization?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Is water level or relative humidity monitoring necessary today or in the future?	Yes or maybe <input type="checkbox"/>	No <input type="checkbox"/>
Do you require comprehensive documentation (e.g. incubation conditions)?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Do you need user management to restrict access to setpoint changes?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Do you require alerts and reminders for regular tasks and maintenance?	Yes <input type="checkbox"/>	No <input type="checkbox"/>
Do you require a door handle on the left side?	Yes <input type="checkbox"/>	No (changeable later) <input type="checkbox"/>



CellXpert C170i

CellXpert C170

Display	VisioNize® touch interface	softkey operated LCD display
High temperature disinfection (HTD)	180 °C standard	140 °C standard
In-field upgradeable options	<ul style="list-style-type: none"> > door handle position > O₂ control > water level sensor/monitoring > relative humidity sensor/monitoring > 4- or 8-segmented inner doors 	<ul style="list-style-type: none"> > door handle position > 4- or 8-segmented inner doors
Capacity	170 L (6.0 ft ³)	
Dimensions external (W × D × H)	71.8 × 71.5 × 90.0 cm (28.3 × 28.1 × 35.4 in)	
Dimensions internal (W × D × H)	53.9 × 44.5 × 69.2 cm (21.2 × 17.5 × 27.2 in)	
Weight w/o accessories	113 kg (249 lb)	
Benchtop (B), Under Bench (U), Floor (F) or Stackable (S)	B, U, F, S (x2)	
Inner door segment options	<ul style="list-style-type: none"> > unsegmented > 4- or 8-segments (factory-installed or in-field upgrade) 	<ul style="list-style-type: none"> > unsegmented > 4-segments (factory-installed) > 8-segments (in-field upgrade)
Temperature range	ambient +4 °C to 50 °C	
Temperature control increment	0.1 °C	
Temperature stability at 37 °C	±0.1 °C	
Temperature accuracy	±0.4 °C	
Temperature sensors	independent, various locations	
CO ₂ range	0.1 – 20 %	
CO ₂ control increment	0.1 %	
CO ₂ stability / accuracy at 5 % CO ₂	±0.1 % / ±0.3 %	
CO ₂ sensor	dual-channel infrared (IR) sensor (high temperature resistant)	
O ₂ range (optional)	1 – 20 % (in-field upgradeable)	–
O ₂ control increment	0.1 %	–
O ₂ stability / accuracy	±0.1 % / ±0.25 %	–
O ₂ sensor	platinum-coated ZrO ₂ (high temperature resistant)	–
Access ports	2	
Pore size in-line gas filter	0.2 µm	
BMS relay	standard	
Number of shelves (included/max)	4/8	3 (4 with 4-segmented door)/8
Copper options	water tray, shelves	
On-board data logging	standard	–
Data export interface	USB, Ethernet	Ethernet (optional, requires VisioNize box)
Remote Device Monitoring and Notifications (VisioNize®)	VisioNize® touch enabled	VisioNize® box enabled

Your local distributor: www.eppendorf.com/contact

Eppendorf SE · Barkhausenweg 1 · 22339 Hamburg
 eppendorf@eppendorf.com · www.eppendorf.com

www.eppendorf.com/co2-incubators